



Ningbo Veken Battery Co., Ltd.

Material Safety Data Sheet

1. PRODUCT & COMPANY IDENTIFICATION

Product Name	Li-ion battery Battery	Model	BL233
Manufacturer	Ningbo Veken Battery Co., Ltd.		
Address	No.2,Area 0212,West Zone,Free Trade Zone,Ningbo, Zhejiang Province, China		
Telephone	+86-0574-86822356		
Issued by	Ningbo Veken Battery Co., Ltd.		
Specification	054953AR 3.7V/1700mAh/6.29Wh		

2. COMPOSITION/INFORMATION ON INGREDIENTS

Composition	Molecular formula	CAS No.	Weight (%)
Lithium Cobalt Oxide	LiCoO ₂	12190-79-3	30-35%
Carbon	C	1333-86-4	20-25%
Electrolyte	LiPF ₆	21324-40-3	1-2%
PVDF	(CH ₂ -CF ₂) _n	24937-79-9	1-2%
Acetylene Black	C	1333-86-4	0.5-1%
SBR	(C ₈ H ₈ .C ₄ H ₆) _x	9003-55-8	0.2-0.8%
EC	C ₃ H ₃ O ₄	96-49-1	5-10%
DMC	C ₃ H ₆ O ₃	616-38-6	5-10%
Aluminum	Al	7429-90-5	10-15%
Copper	Cu	7440-50-8	2-5%
Dissepiment	/	/	2-5%
Others	/	/	2-5%

3. HAZARDS/HEALTH IDENTIFICATION

Health Hazards(Acute and Chronic):

These chemicals are contained in a sealed can. Risk of exposure occurs only if the battery is mechanically or electrolyte and extruded lithium with skin and eyes should be avoided.

Sign/Symptoms of Exposure:

A shorted lithium battery can cause thermal and chemical burns upon contact with the skin.

May be a reproductive hazard.

4. FIRST-AID MEASURES

Inhalation: If battery is burning, leave the area immediately. If exposed to fumes, seek medical attention promptly.

Skin Contact: If battery electrolyte leaks on to the skin, flush the affected area for at least 15 minutes with clean water.

DO NOT attempt to neutralize. Seek medical attention promptly.

5. FIRE-FIGHTING AND EXPLOSION HAZARD DATA

Flammable Properties: N/A



Ningbo Veken Battery Co., Ltd.

Material Safety Data Sheet

Flashpoint: Method;
Autoignition Temperature; Flammable Limits: N/A

Lower flammable limit: Upper flammable limit:

Hazardous Combustion Products: Burning batteries may emit acrid smoke irritating fumes, and toxic fumes of fluoride.

Extinguishing Media: Carbon dioxide (CO₂) or dry chemical fire extinguisher, 10-B:C.

Fire Fighting Instructions:

Personnel: Fight the fire in a defensive mode, while exiting the area. When using a CO₂ fire extinguisher, DO NOT re-enter the area until it has been thoroughly ventilated (i.e., purged) of the CO₂ extinguishing agent.

Firefighters: Use a self-contained breathing apparatus (SCBA).

6. ACCIDENTAL RELEASE MEASURES

Small Spill: If batteries show signs of leaking, AVOID skin or eye contact with the material leaking from the battery. Use chemical resistant rubber gloves and non-flammable absorbent materials for clean-up. Coordinate disposition with the Installation Environmental Office.

7. HANDLING & STORAGE

Handling: Recharge batteries IAW methods specified in applicable technical manuals.

DO NOT:

- Overcharge this battery.

- Abuse, mutilate or short circuit the battery.

Storage: Gain approval for storage areas from the Installation Fire Department. Store batteries in a cool (i.e., 130 F), dry and well ventilated area.

DO NOT:

- Store batteries in direct sunlight or under hot conditions.

- Smoke and keep batteries away from open flame or heat.

- Store batteries in the same stacks with hazardous materials.

- Store batteries in office areas, or other areas where personnel congregate.

Work/Hygienic Practices: Thoroughly wash hands after cleaning-up a battery spill (i.e., leaking or venting batteries).

NO eating, drinking or smoking in battery storage areas.

8. PERSONAL PROTECTION

Personal protective equipment;

Respiration protection: Self-contained breathing apparatus;

Eye protection: Safety glasses

Skin protection: Rubber gloves;

9. PHYSICAL & CHEMICAL PROPERTIES

Boiling Point @ 760 mm Hg (°C): NA



Ningbo Veken Battery Co., Ltd.

Material Safety Data Sheet

Vapor Pressure (mm Hg @ 25 °C): NA

Vapor Density (Air = 1): NA

Density (grams/cc): NA

Percent Volatile by Volume (%): NA

Evaporation Rate (Butyl Acetate = 1): NA

Physical State: NA

Solubility in Water (% by Weight): NA

pH: NA

Appearance and Odor: geometric solid object

10. STABILITY & REACTIVITY

Stable or unstable: Stable

Incompatibility (Materials to avoid) : NA

Hazardous decomposition products: NA

Decomposition temperature (0 °F): NA

Hazardous polymerization: Will Not Occur

Condition to Avoid: Avoid electrical shorting.

11. TOXICOLOGICAL INFORMATION

Acute toxicity: None

Irritation : Irritating to eyes and skin.

Mutagenicity : Not specified.

Chronic toxicity: Not specified.

12. ECOLOGICAL INFORMATION

In case of the worn-out battery was disposed in land, the battery case may be corroded, and leak electrolyte. But, we have no ecological information.

Heavy metal in battery: Mercury(Hg) and Cadmium(Cd) are neither contained nor used in battery.

13. DISPOSAL CONSIDERATION

UTL Lithium-Ion rechargeable cells and batteries contain no toxic metals, only naturally occurring trace elements. Lithium Cells and batteries are exempted from hazardous waste standards under the Universal Waste Regulations, therefore, it is advisable to consult with local state or federal authorities as disposal regulations may vary dependent on location.

14. TRANSPORT INFORMATION

Even classified as lithium ion batteries UN3480 or UN3481 (Contained in Equipment or Packed with Equipment), the product is handled as Non-Dangerous Goods by meeting the UN Recommendations on the Transportation of Dangerous Goods Model Regulations Special Provision SP188. (1)

(a) For a lithium-ion cell, the Watt-hour rating is not more than 20 Wh;



Ningbo Veken Battery Co., Ltd.

Material Safety Data Sheet

(b) For a lithium-ion battery, the Watt-hour rating is not more than 100 Wh.

Lithium ion batteries subject to this provision shall be marked with the Watt-hour rating on the outside case, except those manufactured before 1 January 2009 ;

(c) Each cell or battery is of the type proved to meet the requirements of each test in the UN Manual of Tests and Criteria, Part III, sub-section 38.3 ;

(d) Cells and batteries, except when installed in equipment, shall be packed in inner packagings that completely enclose the cell or battery. Cells and batteries shall be protected so as to prevent short circuits. This includes protection against contact with conductive materials within the same packaging that could lead to a short circuit. The inner packagings shall be packed in strong outer packagings ;

(e) Cells and batteries when installed in equipment shall be protected from damage and short circuit, and the equipment shall be equipped with an effective means of preventing accidental activation. When batteries are installed in equipment, the equipment shall be packed in strong outer packagings constructed of suitable material of adequate strength and design in relation to the packaging's capacity and its intended use unless the battery is afforded equivalent protection by the equipment in which it is contained;

(f) Except for packages containing button cell batteries installed in equipment (including circuit boards), or no more than four cells installed in equipment or no more than two batteries installed in equipment, each package shall be marked with the following:

(i) an indication that the package contain "lithium ion" cells or batteries, as appropriate;

(ii) an indication that the package shall be handled with care and that a flammability hazard exists if the package is damaged;

(iii) an indication that special procedures shall be followed in the event the package is damaged, to include inspection and repacking if necessary; and

(iv) a telephone number for additional information;

(g) Each consignment of one or more packages marked in accordance with paragraph (f) shall be accompanied with a document including the following:

(i) an indication that the package contains "lithium ion" cells or batteries, as appropriate;

(ii) an indication that the package shall be handled with care and that a flammability hazard exists if the package is damaged;

(iii) an indication that special procedures shall be followed in the event the package is damaged, to include inspection and repacking if necessary; and

(iv) a telephone number for additional information;

(h) Except when batteries are installed in equipment, each package shall be capable of withstanding a 1.2 m drop test in any orientation without damage to cells or batteries contained therein, without shifting of the contents so as to allow battery to battery (or cell to cell) contact and without release of contents: and

(i) Except when batteries are contained in or packed with equipment, packages shall not exceed 30 kg gross mass for marine transportation. (not exceed 10kg for air transportation)

For marine transportation the product is handled as Non-Dangerous Goods by meeting the IMO International Maritime Dangerous Goods (IMDG Code) 2017 Edition (Amendment 36-12) SP188 (Same as UN Special Provision SP188 above).

(3) For air transportation the product is handled as Non-Dangerous Goods by meeting the IATA Dangerous Goods Regulations 58 Edition Effective 1 January 2017 Packing Instruction 965-967 General Requirement and Section II/ Section IB (Excepted) and UN Special Provision SP188 above.(2)

(j) Lithium ion batteries identified by manufacturer as being defective for safety reasons, or that have been damaged, that have the potential of producing a dangerous evolution of heat, fire or short circuit are forbidden for transport (e.g. those being returned to the manufacturer for safety reasons).

(k) Each package contains more than four cells or more than two batteries must be labeled with a lithium battery